

ANKERSMID Compressor cooler ACC 85x/86x Ex Series



Application

Ankersmid Compressor Coolers are used to lower the dew point of humid gas to avoid condensate entering into the gas analyser. This unique micro-processor controlled compressor cooler has been designed with a powerful dew point stabiliser. The dew point is set at 3°C. A good and stable gas dew point avoids cross-interference if the analyser is sensitive to H₂O.

Description

The cooler offers precision, safety and long-term stability for extractive analytics. The cooler incorporates a housing suitable for wall-mounting as standard.

The design enables one heat exchanger (mono or dual gas path). The exchanger can be connected in series or parallel following customer requirements.

An electronic system not only monitors the dew point, but also the ambient temperature.

An isolated temperature alarm output for high and low temperature alarm is included as standard.

Available for 230VAC and 115VAC power supply.



* Picture may vary

- **Provide clean dry sample gases to extractive analysers in continuous emission monitoring, process control and engine testing applications**
- **Cooler housing for wall-mounting**
- **Optimise industrial burning processes**
- **Continuously dehumidify gas sample streams**
- **Environment-friendly (CFC free)**
- **Intended for use in Potentially Explosive Atmospheres**
- **According to Directive 94/9/EC**
- **For use in hazardous area Zone 2**



ANKERSMID Compressor cooler
ACC 85x/86x Ex Series



Technical data

Model ACC	85x	86x Ex
Number of gas paths	1 (standard), max. 2 (with double heat exchanger)	
Housing version	Wall-mount or stand alone	
Housing color	RAL 7035 (light-grey)	
Dimensions (W x H x D)	230 x 300 x 355 mm	
Weight (approximately)	18,5 kg	
Peristaltic pump ASR25 for condensate removal	1 pc. (standard)	2 pcs. (standard)
Data per heat exchanger		
Gas flow	1x 250l/h or 2x 125l/h	1x 500l/h or 2x 250l/h
Material of heat exchanger	PVDF	Stainless steel
Maximum pressure	1,5 bar a	100bar a
Pressure drop	6 mbar	8 mbar
Dead volume	67ml (singer heat exchanger), 55ml (double heat exchanger)	
Sample gas inlet	Tube DN 4/6mm	
Sample gas outlet	Tube DN 4/6mm	
Condensate outlet	Tube DN 10/12mm	
Operation data		
Gas inlet dew-point	Max. 70°C	Max. 80°C
Gas inlet temperature	Max. 140°C	Max. 180°C
Cooler capacity	90W	160W
Gas outlet temperature	factory setting: +3°C	
Dew point stability	±1K	
Ambient temperature	+10°C to +40°C	
General electrical data		
Mains connection	approx. 2,3m open wire ends	
Alarm contact	Voltage-free changeover contact, max. 250VAC/2A, min. 5VADC/5mA	
Alarm set points	<0 / >+10°C	
Protection class	IP 20 (EN60529)	
Marking	Ex II 3G Ex ma IIA T3 Ex II 3D Ex ma IIIB T180°C (IEc respectively EN60079)	
Power supply	220...240VAC/50Hz (standard) or 100...115VAC/60Hz	
Electrical protection	External on installation site, fuse characteristic C; 230VAC 6A; 115VAC 10A	
Power consumption	190 VA (depending on configuration, ambient temperature & load)	
Coolant	R134a	



ANKERSMID Compressor cooler
ACC 85x/86x Ex Series



Dimensions

