

OPM 4001

Opacity/Dust Density Monitor

The OPM 4001 Opacity/Dust Density Monitor is a high performance opacity monitoring system with double-pass transmissometer that meets or exceeds Revised 40 CFR 60 B, PS-1 and ASTM D 6216

Features

- **Digital display** instant percent opacity, average percent opacity and time to next calibration
- **Alphanumeric display** for system set-up and fault diagnostics display
- **3 User selectable displays** (instant opacity, average opacity and optical density)
- **U.S. Environmental Protection Agency (EPA) approved** approved zero/span calibration technique
- **Communications** Modbus (RS-485)
- **Stack exit correlation** permanent factory setting
- **Sensor location service module** digital display for percent correlated opacity, T2, manual zero and span initiate and transceiver current loop test jacks
- **Insensitive** to ambient light
- **Double pass** optical system
- **Thru-the-lens** (TTL) alignment
- **Light source** rated for greater than 5 years
- **Electronic modulated** light source
- **Two 4-20mA signals** for instantaneous opacity, and 6 minute average
- **Calibration cycle control** remote, manual and timed
- **System and fault** diagnostics display
- **Path length** of 3-50 feet



Transmissometer/Cover assembly



Standard Controller

OPM 4001 Opacity/Dust Density Monitor

Emerson's Rosemount Analytical OPM 4001 high performance opacity monitoring system with double-pass transmissometer uses field-proven and time-tested optics and circuitry that is simple, yet accurate. Each monitor and all its components are of the highest quality; pre-tested at the factory to your site specifications. The simple instructions will have your monitor up and running in just a few hours.

Emerson has taken the approach to design equipment with accuracy, maintenance and serviceability as the most important features. The Rosemount Analytical OPM 4001 Opacity/Dust Density Monitor is designed with state-of-the-art modular packaging that keeps ease-of-service in mind. The OPM 4001 offers a built-in TTL (through-the-lens) alignment system, where the alignment target can be viewed through a window on the transceiver. Adjustments to changes in alignment are provided by a 3-point alignment system that is integral to the air plenum. This ensures optimum reliability while enabling the system to be easily serviced and maintained in the field by plant service personnel.

Service Module with Digital Display

The service module is used to pass signals to and from the transceiver and control unit, display opacity via digital meter, initiate maintenance zero and span cycles and insertion of external current meter in the transceiver to control unit 4-20 mA loop. The service module is very useful for trouble shooting or during environmental audits as the correlated opacity can be displayed on the DPM. This feature eliminates the necessity for a second person and sometimes difficult communication between the control unit and the sensor locations.

Swing Away Sensor

The swing away sensor makes cleaning the windows a breeze. Both sensors have alignment pins to assure no change in alignment after the sensors have been opened and closed. Large, heavy-duty latches make for an air and water-tight seal. The sensors are attached to the air plenum by two drop-on pivot pins. This makes for easy installation. Should service ever be required, the sensors can be removed; just swing open and lift-off the pivot pins.

Specifications

Control unit

Enclosure

Panel mounted IP65/NEMA4X Dimensions 96x96x64 mm (3.8" x 3.8" x 2.5"). Power 20.4 to 28.8VDC < 10% ripple, 400mA.

Approvals

CE and UL Listed

Digital Display

Selectable pages, LCD backlight

Ambient Temperature Range

0 to +50° C (+32° to 122° F)

Power Requirements

24 VDC +/- 10%

Alarm Time Delay & set point

6 Relays for alarms

Alarm Reset

Manual or Automatic

Analog Outputs

Two 12-bit Analog outputs 4-20mA, Field selectable. 0-100% opacity (mg/m³ and O.D. available with dust option)

Maximum range

Opacity 0-99.9% or Optical Density 0-2000mg/m³ selectable via matrix or menu in the enhanced controller (only)

Calibration check options

Manual zero and span calibrate with dedicated zero reflector or Zero with clear stack condition.

Communications

Modbus – RS485 port

Battery Backup

7 years typical

Transceiver Service module

Display

5/8 inch (15.9 mm), 4-digit LED, selectable for percent opacity and percent transmittance

Local Zero/Span

Manual on demand

Test Jacks

Transceiver to remote control current loop

Diagnostics

Loss of power, current loop open, maintenance mode

Specifications (cont)

Transceiver/Reflector

Enclosure

NEMA 4 watertight enclosure power

Path Length

3-50 feet, 0.9 to 12 meters standard

Optical System

Double pass

Light Source Aging Compensation

Automatic

Light Source Life

> 5 years

Alignment Verification

Passive built-in, through-the lens system

Standard Mounting Flanges

3 inch IPS, 150 lb. flange, standard

Ambient Light Immunity

Solid-state electronic light modulation

Design and Performance

Ambient temperature limits

-40°F to 130°F (-40°C to 54°C)

Maximum process temperature

750°F (400°C)

Maximum stack pressure

+5-inch WC, with the proper installation of purge blowers

Peak and Mean Spectral Response

Photopic; 515 to 585 nm, less than 10% of peak response outside 400 to 700 nm

Relative Spectral Response

<10%

Angle of View

< 4.0° from optical axis

Angle of Projection

< 4.0° from optical axis

Calibration Error/Accuracy

< +1% of full scale

Response time

< 10 second

Zero Drift

< 0.5%

Calibration Drift

< 0.5%

Zero/Span Calibration

Manual or automatic with zero mirror and neutral density filter

Electronic Display Options

Both are EPA 40 CFR B PS-1 and ASTM D 6216 compliant

OPM 4001

- Dual beam measurement
- Automatic or manual online calibration
- User friendly microprocessor controller
- 3 user selectable numerical displays
- Sensor located service module with a digital display for % correlated Opacity and %T²
- Communications via 4-20 mA and RS485 MODBUS



OPM 4001

Additional features with Enhanced Touch screen

- Intuitively designed 5.7" color touch screen user interface with expanded diagnostics
- 5 numerical and 2 trend display screens
- Standard SD card for program and data backup
- Automatic, manual or external online calibrations




Enhanced Touch Screen

Electronic Display Comparison Chart

	w/Touch Screen Option	Standard OPM 4001
ASTMK D 6216 and PS-1 compliant	✓	✓
Communications via 4-20 mA and RS MODBUS	✓	✓
Automatic or manual online calibration	✓	✓
Microprocessor controller	✓	✓
5 numerical display screens	✓	
Intuitively designed icon driven navigation	✓	
Standard 4 analog outputs	✓	
5.7" color touch screen user interface	✓	
Standard program includes % opacity, mg/m ³ and O.D.	✓	
Standard 2GB SD card for program and data backup	✓	
Real-time diagnostics for testing outputs and relays	✓	
Two selectable trend screen displays	✓	
Easy to read color coded fault screen	✓	
User display customization available	✓	


Air purge/Weather cover mechanical installation




*Note 1: The top view represents the transceiver and retro reflector assemblies with their swing clearances. Optional weather covers are not shown.

**Note 2: The side view represents the installation and swing clearance dimensions for the optional weather covers.


Flange to stack installation




Installation Dimensions



OPM 4001 Standard Control Unit



OPM 4001 Service Module



OPM 4001 Enhanced Control Unit

Ordering information

OPM 4001 Opacity/Dust Density Monitor - High performance opacity monitoring system with double-pass transmissometer.

Model	Product Description
OPM 4001	Opacity monitor
Intelligent Electronics	
01	Basic Unit - Digital Display, (2) 4-20mA Outputs, (6) Alarm Relays, RS 232/485, Modbus
02	Enhanced Control Unit with 5.7" LCD graphic color touch screen, icon-driven menu with SD memory card
Transceiver and Path Length	
11	3-15' Path Length
12	>15-21' Path Length
13	>21-40' Path Length
14	>40-50' Path Length
Weather Cover and Blower	
00	None
01	Weather covers only
02	Weather covers and single blower/Tee
03	Weather covers and dual blowers
Zero Jig Type	
01	Zero jig and Neutral Density filters
02	Zero Jig Only
Calculation	
01	Opacity calculation
02	Dust density calculation (mg/m ³), Optional for basic controller, standard on enhanced controller
03	Opacity or Dust Density, User Selectable (requires Enhanced Control Unit)

Ordering Information

Technical Details required at time of order

Customer Company Name: _____

Location:.....

Contact:.....

NOTE: Please submit separate forms per monitor ordered.

The Opacity Monitor you have purchased will be individually built according to the information requested below. While utilizing a basic design each unit is set up and adjusted to meet the requirements set forth by your parameters. The unit is then tested based on these strict requirements to be able to perform at these parameters. If the actual parameters are in fact not the same as those stated below, the unit may need to be returned, readjusted and retested at significant cost to the customer’s account. It is for this reason that we ask you to carefully fill out the information requested in this form.

This completed sheet should be sent with PO to Rosemount Analytical for fastest delivery, otherwise a delayed delivery may be expected. PH: 800-433-6076, FX: 440-914-1262, Email: Gas.CSC@Emerson.com

Information Supplied by (name): _____

NOTE: These items must be filled in! All measurements must be identified as Inches, Ft, mm, cm, etc.

Description	Selection
Unit identification (i.e., boiler 1, Unit 2B, etc.):	_____
Stack exit I.D. (A) on page 2:.....	_____
Flange - to - Flange distance (B) on page 2:.....	_____
I.D. at measuring point (C) page 2:.....	_____
Correlate opacity to “A” or “C” dimension?.....	_____
Sensor: 120 or 220 Vac (50/60 Hz)?.....	_____
Accessory power such as air purge blower if ordered: 120 or 220 Vac (50/60 Hz)	_____

NOTE: If Modbus information is not filled in, our default values will be used. Only Modbus I.D. is field selectable. Other parameters are fixed at time of final test according to the values given above or default. If changes to the communications are required after the system is shipped changes to the program must be made. All labor and shipping costs to make changes will be charged to the customer.

Description	Selection
Communication RS/485, Baud rate (default 9600)	_____
Modbus: Data Bits (default 8)	_____
Parity (default none)	_____
Flow Ctrl (default none).....	_____
Time out (default 0.5 seconds).....	_____
Field selectable Node I.D.# (default 1).....	_____

All measurements must be identified as Inches, Ft, mm, cm, etc.

A, B & C are necessary. Enter measurement information on page 1.

(A) Stack Exit ID Measurement:.....

(B) Flange-to-Flange Measurement: Min/Max: 36 inches to 46 feet (91 cm to 12 meters,) over 15 feet (4.5m) requires optional reflectors.....



(C) ID at Measuring Point: Ratio range of A/2*C must fall between 0.3 and 1.5 _____

The mounting flanges to the stack or duct O.D. should be a minimum of 6 inches to allow for installation of flange bolts.

Measurement tolerance A, B and C must be +/- 1 inch (254mm) or 1% of the total whichever is the smaller. In all cases the mounting flanges are to be installed >2 exit diameters away from the stack exit because of Gas flow turbulence.

Ordering Information (con't)

Choose the drawing below that best fits the installation.



Rosemount Analytical

Headquarters & Liquid Analytical
2400 Barranca Parkway
Irvine, CA 92606
United States
Phone: 1.800.854.8257
Fax: 1.949.474.7250

 www.facebook.com/Emerson-RosemountAnalytical

 twitter.com/RAIhome.com

 www.analyticexpert.com

 youtube.com/user/rosemountanalytical

Rosemount Analytical

Gas Chromatographs & Service Center
10241 West Little York, Suite 200
Houston, Texas 77040
United States
Phone: 1.866.422.3683
Fax: 1.713.827.3865

Rosemount Analytical

Process Gas & Combustion Center
6565-P Davis Industrial Pkwy
Solon, OH 44139
United States
Phone: 1.800.433.6076
Fax: 1.440.914.1262

Rosemount Analytical – Latin America

Emerson Process Management
10241 West Little York, Suite 200
Houston, Texas 77040
United States
Phone: 1.866.422.3683
Fax: 1.713.827.3865

Rosemount Analytical - Europe

Emerson Process Management Services Ltd.
Blegistrasse 21
PO Box 1046
CH 6341 Baar
Switzerland
Phone: 41.41.768.6111
Fax: 41.41.761.8740

**Emerson Process Management
Distribution Limited**

P.O. Box 105958
Abu Dhabi
UAE
Phone: +971 2 6972072
Fax: +971 2 5550364

Rosemount Analytical – Asia Pacific

Emerson Process Management
Asia Pacific Private Ltd.
1 Pandan Crescent
Singapore 128461
Republic of Singapore
Phone: 65.6.777.8211
Fax: 65.6.777.0947

© 2013 Emerson Process Management. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand name is a mark of one of the Emerson Process Management family of companies. All other marks are the property of their respective owners.

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.